



SCHEIBE DISTANZRING



Einbaubeispiel



244.10.



Werkstoff:
C 45 vergütet

244.10. Scheibe


d ₁	d ₂	s ₁	d ₁	d ₂	s ₁	d ₁	d ₂	s ₁	d ₁	d ₂	s ₁
6,4	17	3	13	35	8	21	44	8	26	58	6
8,4	17	3	13	46	8	21	45	8	26	70	12
8,4	23	4	13,4	23	4	21	45	16	26	80	12
8,5	20	4	16,4	26	4	21	46	6	31	68	8
9	26	4	17	35	4	21	49	6	31	68	10
10,5	25	4	17	35	6	21	50	10	31	80	12
10,5	25	5	17	36	4	21	65	8	31	100	15
10,5	26	4	17	36	13	21	70	12	32	90	15
10,5	28	4	17	37	6	22	65	12	32	92	15
10,5	30	5	17	38	6	22	68	12	37	80	8
11	30	6	17	40	6	25	46	10	43	92	8
11	36	6	17	50	6	25	55	10			
12,5	28	4	17	50	10	25	56	10			
13	30	5	17	58	10	25	65	12			
13	35	5	20,4	30	5	25	70	10			
13	30	6	21	42	8	25	90	12			

Bestell-Beispiel:


Scheibe	=	244.10.
Innendurchmesser d ₁	6,4 mm	= 064.
Außendurchmesser d ₂	17 mm	= 017.
Dicke s ₁	3 mm	= 03
Bestell-Nummer	=	244.10. 064.017.03



Einbaubeispiel



244.11.



Werkstoff:
St 35.4 oberflächengehärtet

244.11. Distanzring

Feder ø	20 25	32 40
d ₁	20	30
d ₂	25	38
Bestellcode	25	40

Bestell-Beispiel:

Distanzring	=	244.11.
Bestellcode Durchmesser	40 mm	= 40
Bestell-Nummer	=	244.11. 40