



HEADED GUIDE BUSH, SINTERED FERRITE CARBONITRIDED
WITH LONG-TERM LUBRICATION, ISO 9448-6

2081.32.

Mounting example



Material:

Sintered ferrite of high purity, carbonitrided, long-term lubrication

Execution:

Bearing surfaces and outside diameter precision ground.

Note:

The attachment is with 3 Screw clamp, from $\varnothing d_1 = 38$ with 4 Screw clamp, which are included in delivery (Order No: 207.45 - Screw clamp incl. socket cap screw DIN 6912, Head $\varnothing 13$).

☞ Notes on sliding type guides at the beginning of chapter D.

*☞ Bearing clearance see pairing classification at the beginning of chapter D.

☞ Matching guide combinations, see selection matrix at the beginning of chapter D.

☞ Assembly guide lines / Dimensional requirements and tolerances at the end of chapter D.

Tolerance range:

yellow = .10

green = .20

red = .30

2081.32. Headed guide bush, sintered ferrite carbonitrided with long-term lubrication, ISO 9448-6

d ₁	24 25	30 32	38 40	48 50
d ₃	40	48	58	70
d ₄	40	48	58	70
d ₅	48	56	66	80
d ₆	60	67	77	91
d ₇	72.7	79.7	89.7	103.7
d ₈	46	53	63	77
a	22.65	24.4	35.3	40.2
a ₁	33.4	36.4	35.3	40.2
l ₁	80	93	110	131
l ₂	30	37	47	60
l ₃	50	56	63	71

Ordering Code (example):

Headed guide bush, sintered ferrite carbonitrided with
long-term lubrication, ISO 9448-6

= 2081.32.

Diameter of conduit d₁ 38 mm = 038.

Classification TOL yellow = 10

Order No = 2081.32. 038. 10