


SPRING PLUNGER, WITH SPRING LOADED PIN, WITH SLOT, STANDARD SPRING FORCE

2472.05.



2472.05. Spring plunger, with spring loaded pin, with slot, standard spring force

Order No	d ₁	d ₂	l	s	Spring force [N]	
					initial	final
2472.05.004	4	1.8	9	1.5	4.5	12.5
2472.05.005	5	2.4	12	2	5	13
2472.05.006	6	2.7	14	2	6	17
2472.05.008	8	3.8	16	2	16	33
2472.05.010	10	4.5	19	2.5	19	42
2472.05.012	12	6.2	22	3.5	22	57
2472.05.016	16	8.5	24	4.5	38	78
2472.05.020	20	10	30	6.5	39	81
2472.05.024	24	13	34	8	72	155


Material:

Sleeve: Free machining steel, burnished
 Pin: Free machining steel hardened, burnished
 Spring: Nirosta

Note:

For locking and for pressing upwards or downwards.
 Temperature operating range: max. 250°C

2472.35.



2472.35. Spring plunger, with spring loaded pin, with slot, standard spring force

Order No	d ₁	d ₂	l	s	Spring force [N]	
					initial	final
2472.35.004	4	1.8	9	1.5	4.5	12.5
2472.35.005	5	2.4	12	2	5	13
2472.35.006	6	2.7	14	2	6	17
2472.35.008	8	3.8	16	2	16	33
2472.35.010	10	4.5	19	2.5	19	42
2472.35.012	12	6.2	22	3.5	22	57
2472.35.016	16	8.5	24	4.5	38	78
2472.35.020	20	10	30	6.5	39	81
2472.35.024	24	13	34	8	72	155

Material:

Sleeve: Inox 1.4305
 Pin: Inox 1.4305
 Spring: Nirosta

Note:

For locking and for pressing upwards or downwards.
 Temperature operating range: max. 250°C