


GOUPILLE CYLINDRIQUE AVEC TARAUDAGE, SELON DIN EN ISO 8735

2361.1.



Matière :

Acier
Dureté 60 ± 2 HRC

Exécution :

trempées, finement rectifiées

2361.1. Goupille cylindrique avec taraudage, selon DIN EN ISO 8735

d ₁	d ₂	t ₁	l ₂	r	l ₁	8	10	12	14	16	18	20	22	24	26	28	30	32	36	40	45	50	55	60	70	80	90	100	120
4	M2,5	4,5	1,3	4			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
5	M3	5	1,7	5		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
6	M4	6	2,1	6				●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
8	M5	8	2,6	8						●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
10	M6	10	3	10						●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
12	M6	10	3,8	12							●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
14	M8	12	4	14								●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
16	M8	12	4,7	16									●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
20	M10	16	6	20											●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

Exemple de commande :

Goupille cylindrique avec taraudage, selon DIN EN ISO 8735	=	2361.1.
Diamètre d ₁	10 mm =	1000.
Longueur l ₁	16 mm =	016
N° de commande	=	2361.1. 1000. 016